
PyDriller Documentation

Release 1.0

Davide Spadini

Oct 22, 2018

Contents

1	Overview / Install	1
1.1	Requirements	1
1.2	Installing PyDriller	1
1.3	Source Code	1
1.4	How to cite PyDriller	2
2	Getting Started	3
3	Configuration	5
3.1	Selecting the Commit Range	5
3.2	Filtering commits	6
4	Commit Object	7
5	Modifications	9
6	Git Repository	11
7	API Reference	13
7.1	GitRepository	13
7.2	RepositoryMining	15
7.3	Commit	16
7.4	Developer	18
8	Indices and tables	19
	Python Module Index	21

PyDriller is a Python framework that helps developers on mining software repositories. With PyDriller you can easily extract information from any Git repository, such as commits, developers, modifications, diffs, and source codes, and quickly export CSV files.

1.1 Requirements

- [Python 3.4](#) or newer
- [Git](#)

1.2 Installing PyDriller

Installing PyDriller is easily done using [pip](#). Assuming it is installed, just run the following from the command-line:

```
# pip install pydriller
```

This command will download the latest version of GitPython from the [Python Package Index](#) and install it to your system. This will also install the necessary dependencies.

1.3 Source Code

PyDriller's git repo is available on GitHub, which can be browsed at:

- <https://github.com/ishepard/pydriller>

and cloned using:

```
$ git clone https://github.com/ishepard/pydriller
$ cd pydriller
```

Optionally (but suggested), make use of virtualenv:

```
$ virtualenv -p python3 venv
$ source venv/bin/activate
```

Install the requirements:

```
$ pip install -r requirements
$ unzip test-repos.zip
```

and run the tests using pytest:

```
$ pytest
```

1.4 How to cite PyDriller

```
@inbook{PyDriller,
  title = "PyDriller: Python Framework for Mining Software Repositories",
  abstract = "Software repositories contain historical and valuable information_
↳about the overall development of software systems. Mining software repositories_
↳(MSR) is nowadays considered one of the most interesting growing fields within_
↳software engineering. MSR focuses on extracting and analyzing data available in_
↳software repositories to uncover interesting, useful, and actionable information_
↳about the system. Even though MSR plays an important role in software engineering_
↳research, few tools have been created and made public to support developers in_
↳extracting information from Git repository. In this paper, we present PyDriller, a_
↳Python Framework that eases the process of mining Git. We compare our tool against_
↳the state-of-the-art Python Framework GitPython, demonstrating that PyDriller can_
↳achieve the same results with, on average, 50% less LOC and significantly lower_
↳complexity.URL: https://github.com/ishepard/pydrillerMaterials: https://doi.org/10.
↳5281/zenodo.1327363Pre-print: https://doi.org/10.5281/zenodo.1327411",
  author = "Spadini, Davide and Aniche, Maurício and Bacchelli, Alberto",
  year = "2018",
  doi = "10.1145/3236024.3264598",
  booktitle = "The 26th ACM Joint European Software Engineering Conference and_
↳Symposium on the Foundations of Software Engineering (ESEC/FSE)",
}
```

CHAPTER 2

Getting Started

Using PyDriller is very simple. You only need to create *RepositoryMining*: this class will receive in input the path to the repository and will return a generator that iterates over the commits. For example:

```
for commit in RepositoryMining('path/to/the/repo').traverse_commits():
    print('Hash {}, author {}'.format(commit.hash, commit.author.name))
```

will print the name of the developers for each commit.

Inside *RepositoryMining*, you will have to configure which projects to analyze, for which commits, for which dates etc. For all the possible configurations, have a look at [Configuration](#).

Let's make another example: print all the modified files for every commit. This does the magic:

```
for commit in RepositoryMining('path/to/the/repo').traverse_commits():
    for modification in commit.modifications:
        print('Author {} modified {} in commit {}'.format(commit.author.name,
            ↪modification.filename, commit.hash))
```

That's it!

Behind the scenes, PyDriller opens the Git repository and extracts all the necessary information. Then, the framework returns a generator that can iterate over the commits.

Ok, let's try a more difficult problem: let's count how many commits contain the word “bug” in the message. We can do it like this:

```
count = 0
for commit in RepositoryMining('path/to/the/repo').traverse_commits():
    if 'bug' in commit.msg:
        count += 1
```

Furthermore, PyDriller can calculate structural metrics of every file changed in a commit. To calculate these metrics, Pydriller relies on [Lizard](#), a powerful tool that can analyze source code of many different programming languages, both at class and method level!

```
for commit in RepositoryMining('path/to/the/repo').traverse_commits():
    for mod in commit.modifications:
        print('{} has complexity of {}, and it contains {} methods'.format(
            mod.filename, mod.complexity, len(mod.methods))
```


One of the main advantage of using PyDriller to mine software repositories, is that is highly configurable. Let's start with selecting which commit to analyze.

3.1 Selecting the Commit Range

By default, PyDriller executes the visitor for all the commits in the repository. However, filters can be applied to *RepositoryMining* to visit *only specific* commits.

- *single: str*: single hash of the commit. The visitor will be called only on this commit

FROM:

- *since: datetime*: only commits after this date will be analyzed
- *from_commit: str*: only commits after this commit hash will be analyzed
- *from_tag: str*: only commits after this commit tag will be analyzed

TO:

- *to: datetime*: only commits up to this date will be analyzed
- *to_commit: str*: only commits up to this commit hash will be analyzed
- *to_tag: str*: only commits up to this commit tag will be analyzed

Examples:

```
# Analyze single commit
RepositoryMining('path/to/the/repo', single='6411e3096dd2070438a17b225f44475136e54e3a
↪').traverse_commits()

# Since 8/10/2016
RepositoryMining('path/to/the/repo', since=datetime(2016, 10, 8, 17, 0, 0)).traverse_
↪commits()
```

(continues on next page)

(continued from previous page)

```
# Between 2 dates
dt1 = datetime(2016, 10, 8, 17, 0, 0)
dt2 = datetime(2016, 10, 8, 17, 59, 0)
RepositoryMining('path/to/the/repo', since=dt1, to=dt2).traverse_commits()

# Between tags
from_tag = 'tag1'
to_tag = 'tag2'
RepositoryMining('path/to/the/repo', from_tag=from_tag, to_tag=to_tag).traverse_
↳ commits()

# Up to a date
dt1 = datetime(2016, 10, 8, 17, 0, 0, tzinfo=to_zone)
RepositoryMining('path/to/the/repo', to=dt1).traverse_commits()

# !!!!! ERROR !!!!! THIS IS NOT POSSIBLE
RepositoryMining('path/to/the/repo', from_tag=from_tag, from_commit=from_commit).
↳ traverse_commits()
```

IMPORTANT: it is **not** possible to configure more than one filter of the same category (for example, more than one *from*). It is also **not** possible to have the *single* filter together with other filters!

3.2 Filtering commits

PyDriller comes with a set of common commit filters that you can apply:

- *only_in_branches*: *List[str]*: only analyses commits that belong to certain branches.
- *only_in_main_branch*: *bool*: only analyses commits that belong to the main branch of the repository.
- *only_no_merge*: *bool*: only analyses commits that are not merge commits.
- *only_modifications_with_file_types*: *List[str]*: only analyses commits in which at least one modification was done in that file type, e.g., if you pass “java”, then, the it will visit only commits in which at least one Java file was modified; clearly, it will skip other commits.

Examples:

```
# Only commits in main branch
RepositoryMining('path/to/the/repo', only_in_main_branch=True).traverse_commits()

# Only commits in main branch and no merges
RepositoryMining('path/to/the/repo', only_in_main_branch=True, only_no_merge=True).
↳ traverse_commits()

# Only commits that modified a java file
RepositoryMining('path/to/the/repo', only_modifications_with_file_types=['.java']).
↳ traverse_commits()
```

CHAPTER 4

Commit Object

A Commit contains a hash, a committer (name and email), an author (name, and email), a message, the authored date, committed date, a list of its parent hashes (if it's a merge commit, the commit has two parents), and the list of modification.

For example:

```
for commit in RepositoryMining('path/to/the/repo').traverse_commits():
    print(
        'Hash: {}'.format(commit.hash),
        'Author: {}'.format(commit.author.name),
        'Committer: {}'.format(commit.committer.name),
        'Author date: {}'.format(commit.author_date.strftime("%Y-%m-%d %H:%M:%S")),
        'Message: {}'.format(commit.msg),
        'Merge: {}'.format(commit.merge),
        'In main branch: {}'.format(commit.in_main_branch)
    )
```

Modifications

You can get the list of modified files, as well as their diffs and current source code. To that, all you have to do is to get the list of *Modifications* that exists inside *Commit*. A modification object has the following fields:

- **old_path**: old path of the file (can be `_None_` if the file is added)
- **new_path**: new path of the file (can be `_None_` if the file is deleted)
- **change_type**: type of the change: can be Added, Deleted, Modified, or Renamed.
- **diff**: diff of the file as Git presents it (e.g., starting with `@@ xx,xx @@`).
- **source_code**: source code of the file (can be `_None_` if the file is deleted)
- **added**: number of lines added
- **removed**: number of lines removed
- **nloc**: Lines Of Code (LOC) of the file
- **complexity**: Cyclomatic Complexity of the file
- **token_count**: Number of Tokens of the file
- **methods**: list of methods of the file. The list might be empty if the programming language is not supported or if the file is not a source code file.

For example:

```
for commit in RepositoryMining('path/to/the/repo').traverse_commits():
    for m in commit.modifications:
        print(
            "Author {}".format(commit.author.name),
            " modified {}".format(m.filename),
            " with a change type of {}".format(m.change_type.name),
            " and the complexity is {}".format(m.complexity)
        )
```


CHAPTER 6

Git Repository

GitRepository is a wrapper for the most common utilities of Git. It receives in input the path to repository, and it takes care of the rest. For example, with GitRepository you can checkout a specific commit:

```
gr = GitRepository('test-repos/git-1/')
gr.checkout('a7053a4dcd627f5f4f213dc9aa002eb1caf926f8')
```

However, **be careful!** Git checkout changes the state of the repository on the hard disk, hence you should not use this command if other processes (maybe threads? or multiple repository mining?) read from the same repository.

GitRepository also contains a function to parse the a *diff*, very useful to obtain the list of lines added or deleted for future analysis. For example, if we run this:

```
diff = '@@ -2,6 +2,7 @@ aa'+\
      ' bb'+\
      '-cc'+\
      ' log.info(\"aa\")'+\
      '+log.debug(\"b\")'+\
      ' dd'+\
      ' ee'+\
      ' ff'
gr = GitRepository('test-repos/test1')
parsed_lines = gr.parse_diff(diff)

added = parsed_lines['added']
deleted = parsed_lines['deleted']

print('Added: {}'.format(added))      # result: Added: [(4, 'log.debug("b")')]
print('Deleted: {}'.format(deleted))  # result: Deleted: [(3, 'cc')]
```

the result is:

```
Added: [(4, 'log.debug("b")')]
Deleted: [(3, 'cc')]
```

Another very useful API (especially for researchers ;)) is the one that, given a commit, allows you to retrieve all the commits that last “touched” the modified lines of the file (if you pass a bug fixing commit, it will retrieve the bug inducing). Let’s see an example:

```
# commit abc modified line 1 of file A
# commit def modified line 2 of file A
# commit ghi modified line 3 of file A
# commit lmn deleted lines 1 and 2 of file A

gr = GitRepository('test-repos/test5')

commit = gr.getcommit('lmn')
buggy_commits = gr.get_commits_last_modified_lines(commit)
print(buggy_commits)          # result: (abc, def)
```

Since in commit **lmn** 2 lines were deleted (line 1 and 2), PyDriller can retrieve the commits in which those lines were last modified (in our example, commit **abc** and **def**).

Isn’t it cool? :)

Checkout the API reference of this class for the complete list of the available functions.

7.1 GitRepository

class pydriller.git_repository.**GitRepository** (*path: str*)

__init__ (*path: str*)

Init the Git Repository.

Parameters **path** (*str*) – path to the repository

__module__ = 'pydriller.git_repository'

checkout (*_hash: str*) → None

Checkout the repo at the specified commit. BE CAREFUL: this will change the state of the repo, hence it should *not* be used with more than 1 thread.

Parameters **_hash** – commit hash to checkout

files () → List[str]

Obtain the list of the files (excluding .git directory).

Returns List[str], the list of the files

get_commit (*commit_id: str*) → pydriller.domain.commit.Commit

Get the specified commit.

Parameters **commit_id** (*str*) – hash of the commit to analyze

Returns Commit

get_commit_from_gitpython (*commit: git.objects.commit.Commit*) → pydriller.domain.commit.Commit

Build a PyDriller commit object from a GitPython commit object. This is internal of PyDriller, I don't think users generally will need it.

Parameters **commit** (*GitCommit*) – GitPython commit

Returns Commit commit: PyDriller commit

get_commit_from_tag (*tag: str*) → `pydriller.domain.commit.Commit`
Obtain the tagged commit.

Parameters **tag** (*str*) – the tag

Returns `Commit` commit: the commit the tag referred to

get_commits_last_modified_lines (*commit: pydriller.domain.commit.Commit, modification: pydriller.domain.commit.Modification = None*) → `Set[str]`

Given the `Commit` object, returns the set of commits that last “touched” the lines that are modified in the files included in the commit. It applies SZZ. The algorithm works as follow: (for every file in the commit)

1- obtain the diff

2- obtain the list of deleted lines

3- blame the file and obtain the commits were those lines were added

Can also be passed as parameter a single `Modification`, in this case only this file will be analyzed.

Parameters

- **commit** (`Commit`) – the commit to analyze
- **modification** (`Modification`) – single modification to analyze

Returns the set containing all the bug inducing commits

get_head () → `pydriller.domain.commit.Commit`
Get the head commit.

Returns `ChangeSet` of the head commit

get_list_commits () → `List[pydriller.domain.commit.Commit]`
Return the list of all the commits in the repo.

Returns `List[ChangeSet]`, the list of all the commits in the repo

parse_diff (*diff: str*) → `Dict[str, List[Tuple[int, str]]]`

Given a diff, returns a dictionary with the added and deleted lines. The dictionary has 2 keys: “added” and “deleted”, each containing the corresponding added or deleted lines. For both keys, the value is a list of `Tuple (int, str)`, corresponding to (number of line in the file, actual line).

Parameters **diff** (*str*) – diff of the commit

Returns Dictionary

reset () → `None`

Reset the state of the repo, checking out the main branch and discarding local changes (-f option).

total_commits () → `int`

Calculate total number of commits.

Returns the total number of commits

7.2 RepositoryMining

```
class pydriller.repository_mining.RepositoryMining (path_to_repo: str, single: str =
                                                    None, since: datetime.datetime
                                                    = None, to: datetime.datetime
                                                    = None, from_commit: str =
                                                    None, to_commit: str = None,
                                                    from_tag: str = None, to_tag: str
                                                    = None, reversed_order: bool =
                                                    False, only_in_main_branch: bool
                                                    = False, only_in_branches:
                                                    List[str] = None,
                                                    only_modifications_with_file_types:
                                                    List[str] = None, only_no_merge:
                                                    bool = False)
```

```
__init__(path_to_repo: str, single: str = None, since: datetime.datetime = None, to: date-
time.datetime = None, from_commit: str = None, to_commit: str = None, from_tag: str
= None, to_tag: str = None, reversed_order: bool = False, only_in_main_branch: bool =
False, only_in_branches: List[str] = None, only_modifications_with_file_types: List[str] =
None, only_no_merge: bool = False)
```

Init a repository mining.

Parameters

- **path_to_repo** (*str*) – absolute path to the repository you have to analyze
- **single** (*str*) – hash of a single commit to analyze
- **since** (*datetime*) – starting date
- **to** (*datetime*) – ending date
- **from_commit** (*str*) – starting commit (only if *since* is None)
- **to_commit** (*str*) – ending commit (only if *to* is None)
- **from_tag** (*str*) – starting the analysis from specified tag (only if *since* and *from_commit* are None)
- **to_tag** (*str*) – ending the analysis from specified tag (only if *to* and *to_commit* are None)
- **reversed_order** (*bool*) – whether the commits should be analyzed in reversed order
- **only_in_main_branch** (*bool*) – whether only commits in main branch should be analyzed
- **only_in_branches** (*List[str]*) – only commits in these branches will be analyzed
- **only_modifications_with_file_types** (*List[str]*) – only modifications with that file types will be analyzed
- **only_no_merge** (*bool*) – if True, merges will not be analyzed

```
__module__ = 'pydriller.repository_mining'
```

```
traverse_commits() → Generator[[pydriller.domain.commit.Commit, None], None]
```

Analyze all the specified commits (all of them by default), returning a generator of commits.

7.3 Commit

```
class pydriller.domain.commit.Commit(commit: git.objects.commit.Commit, path: str,
                                     main_branch: str)
```

```
    __init__(commit: git.objects.commit.Commit, path: str, main_branch: str) → None
        Create a commit object.
```

```
    __module__ = 'pydriller.domain.commit'
```

```
    author
        Return the author of the commit as a Developer object.
```

```
        Returns author
```

```
    author_date
        Return the authored datetime.
```

```
        Returns datetime author_datetime
```

```
    author_timezone
        Author timezone expressed in seconds from epoch.
```

```
        Returns int timezone
```

```
    branches
        Return the set of branches that contain the commit.
```

```
        Returns set(str) branches
```

```
    committer
        Return the committer of the commit as a Developer object.
```

```
        Returns committer
```

```
    committer_date
        Return the committed datetime.
```

```
        Returns datetime committer_datetime
```

```
    committer_timezone
        Author timezone expressed in seconds from epoch.
```

```
        Returns int timezone
```

```
    hash
        Return the SHA of the commit.
```

```
        Returns str hash
```

```
    in_main_branch
        Return True if the commit is in the main branch, False otherwise.
```

```
        Returns bool in_main_branch
```

```
    merge
        Return True if the commit is a merge, False otherwise.
```

```
        Returns bool merge
```

```
    modifications
        Return a list of modified files.
```

```
        Returns List[Modification] modifications
```

msg

Return commit message.

Returns str commit_message

parents

Return the list of parents SHAs.

Returns List[str] parents

class pydriller.domain.commit.**Method**(func)

__init__(func)

Initialize a method object. This is calculated using Lizard: it parses the source code of all the modifications in a commit, extracting information of the methods contained in the file (if the file is a source code written in one of the supported programming languages).

__module__ = 'pydriller.domain.commit'

class pydriller.domain.commit.**Modification**(old_path: str, new_path: str, change_type: pydriller.domain.commit.ModificationType, diff_and_sc: Dict[str, str])

__init__(old_path: str, new_path: str, change_type: pydriller.domain.commit.ModificationType, diff_and_sc: Dict[str, str])

Initialize a modification. A modification carries on information regarding the changed file. Normally, you shouldn't initialize a new one.

__module__ = 'pydriller.domain.commit'

added

Return the total number of added lines in the file.

Returns int lines_added

complexity

Calculate the Cyclomatic Complexity of the file.

Returns Cyclomatic Complexity of the file

filename

Return the filename. Given a path-like-string (e.g. "/Users/dspadini/pydriller/myfile.py") returns only the filename (e.g. "myfile.py")

Returns str filename

methods

Return the list of methods in the file. Every method contains various information like complexity, loc, name, number of parameters, etc.

Returns list of methods

nloc

Calculate the LOC of the file.

Returns LOC of the file

removed

Return the total number of deleted lines in the file.

Returns int lines_deleted

token_count

Calculate the token count of functions.

Returns token count

```
class pydriller.domain.commit.ModificationType
    An enumeration.

    ADD = (1,)
    COPY = (2,)
    DELETE = (4,)
    MODIFY = 5
    RENAME = (3,)

    __module__ = 'pydriller.domain.commit'
```

7.4 Developer

```
class pydriller.domain.developer.Developer (name: str, email: str)

    __init__ (name: str, email: str)
        Class to identify a developer.

        Parameters
        • name (str) – name and surname of the developer
        • email (str) – email of the developer

    __module__ = 'pydriller.domain.developer'
```

CHAPTER 8

Indices and tables

- `genindex`
- `modindex`
- `search`

p

- `pydriller.domain.commit`, [16](#)
- `pydriller.domain.developer`, [18](#)
- `pydriller.git_repository`, [13](#)
- `pydriller.repository_mining`, [15](#)

Symbols

__init__() (pydriller.domain.commit.Commit method), 16
 __init__() (pydriller.domain.commit.Method method), 17
 __init__() (pydriller.domain.commit.Modification method), 17
 __init__() (pydriller.domain.developer.Developer method), 18
 __init__() (pydriller.git_repository.GitRepository method), 13
 __init__() (pydriller.repository_mining.RepositoryMining method), 15
 __module__ (pydriller.domain.commit.Commit attribute), 16
 __module__ (pydriller.domain.commit.Method attribute), 17
 __module__ (pydriller.domain.commit.Modification attribute), 17
 __module__ (pydriller.domain.commit.ModificationType attribute), 18
 __module__ (pydriller.domain.developer.Developer attribute), 18
 __module__ (pydriller.git_repository.GitRepository attribute), 13
 __module__ (pydriller.repository_mining.RepositoryMining attribute), 15

A

ADD (pydriller.domain.commit.ModificationType attribute), 18
 added (pydriller.domain.commit.Modification attribute), 17
 author (pydriller.domain.commit.Commit attribute), 16
 author_date (pydriller.domain.commit.Commit attribute), 16
 author_timezone (pydriller.domain.commit.Commit attribute), 16

B

branches (pydriller.domain.commit.Commit attribute), 16

C

checkout() (pydriller.git_repository.GitRepository method), 13
 Commit (class in pydriller.domain.commit), 16
 committer (pydriller.domain.commit.Commit attribute), 16
 committer_date (pydriller.domain.commit.Commit attribute), 16
 committer_timezone (pydriller.domain.commit.Commit attribute), 16
 complexity (pydriller.domain.commit.Modification attribute), 17
 COPY (pydriller.domain.commit.ModificationType attribute), 18

D

DELETE (pydriller.domain.commit.ModificationType attribute), 18
 Developer (class in pydriller.domain.developer), 18

F

filename (pydriller.domain.commit.Modification attribute), 17
 files() (pydriller.git_repository.GitRepository method), 13

G

get_commit() (pydriller.git_repository.GitRepository method), 13
 get_commit_from_gitpython() (pydriller.git_repository.GitRepository method), 13
 get_commit_from_tag() (pydriller.git_repository.GitRepository method), 13
 get_commits_last_modified_lines() (pydriller.git_repository.GitRepository method), 14
 get_head() (pydriller.git_repository.GitRepository method), 14

`get_list_commits()` (pydriller.git_repository.GitRepository method), 14

`traverse_commits()` (pydriller.repository_mining.RepositoryMining method), 15

`GitRepository` (class in `pydriller.git_repository`), 13

H

`hash` (pydriller.domain.commit.Commit attribute), 16

I

`in_main_branch` (pydriller.domain.commit.Commit attribute), 16

M

`merge` (pydriller.domain.commit.Commit attribute), 16

`Method` (class in `pydriller.domain.commit`), 17

`methods` (pydriller.domain.commit.Modification attribute), 17

`Modification` (class in `pydriller.domain.commit`), 17

`modifications` (pydriller.domain.commit.Commit attribute), 16

`ModificationType` (class in `pydriller.domain.commit`), 18

`MODIFY` (pydriller.domain.commit.ModificationType attribute), 18

`msg` (pydriller.domain.commit.Commit attribute), 16

N

`nloc` (pydriller.domain.commit.Modification attribute), 17

P

`parents` (pydriller.domain.commit.Commit attribute), 17

`parse_diff()` (pydriller.git_repository.GitRepository method), 14

`pydriller.domain.commit` (module), 16

`pydriller.domain.developer` (module), 18

`pydriller.git_repository` (module), 13

`pydriller.repository_mining` (module), 15

R

`removed` (pydriller.domain.commit.Modification attribute), 17

`RENAME` (pydriller.domain.commit.ModificationType attribute), 18

`RepositoryMining` (class in `pydriller.repository_mining`), 15

`reset()` (pydriller.git_repository.GitRepository method), 14

T

`token_count` (pydriller.domain.commit.Modification attribute), 17

`total_commits()` (pydriller.git_repository.GitRepository method), 14